

OPTIMIX 20

SINGLE-PHASE - 3 KW

Spraying machines for slurry products | reference : 912000600A



Versatile machine ideal for spraying conventional, pre-mixed surface mortars, special products and cement screed.

This machine is compatible with any product with a grain size not exceeding 6 mm, with a drying time of minimum 60 min and a density enabling it to flow through the hose.

TECHNICAL DATA

| | |
|---------------------------------|------------------|
| Hopper capacity | 80 L |
| Power supply | 400 V - 50 Hz |
| Motor power | 3 kW |
| Compressor flow rate | 250 L/min |
| Variable speed | yes |
| Compressor motor power | 0.75 kW |
| Spraying flow rate | 0 to 17 L/min |
| Max. spraying distance | 40 meters* |
| Max. pressure | 3.5 bar |
| Max. grain size | 6 mm |
| Integrated compressor (cat. C5) | 8021007300 |
| Dimensions (l x w x h) | 140 x 70 x 81 cm |
| Weight | 185 kg |

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Two 35x50 10 LM spraying hoses with 1"1/4 couplings
- Classic spray lance
- 20 LM neoprene 3x6 power cord with plug
- 13x19 21 LM air hose with GEKA coupling
- Maintenance kit

MIXER[®]